

HONEYWELL MIDAS[®]-M

Gas Monitoring System

Bringing new visibility, reliability, and ease-of-use to gas detection in semiconductor processing and industrial manufacturing.

An easy-to-use, cost-effective addition to the Honeywell gas detection portfolio, the Honeywell Midas[®]-M Gas Detector uses reliable sensor technology to detect more than 35 key toxic, ambient, and flammable gases — easily, quickly, and error-free.

The device monitors points up to 30 meters (100 feet) away while using patented technology to regulate flow rates and ensure error-free gas detection.

The standard power supply and communications capabilities include three onboard relays (Form C), 0 mA to 21 mA analog output, and Modbus[®]/TCP Ethernet digital outputs for easy connectivity to control and alarm systems' ports for optimal connectivity and service interaction.

With flexible features and options, the Midas-M Gas Detector works right out of the box and configures easily to meet your needs. Each plug-and-play sensor cartridge is pre-calibrated, so it's ready when you are. That means longer sensor life, quick-and-easy replacement, and no operator error due to incorrect or depleted sensors. With the Midas-M Gas Detector, customers can get extended sensor calibration periods, patented diagnostics, and lower cost of ownership.



APPLICATIONS

- Semiconductor processing
- Light industrial manufacturing
- University laboratories
- Aerospace
- Wastewater

FEATURES AND BENEFITS



CLEAR VISIBILITY

The Midas-M Gas Detector is equipped with bright LEDs and an intuitive interface that provides instant alerts to gas readings or alarm levels.



CALIBRATION COMPLETED

Factory-calibrated sensors reduce need for frequent gas testing.



EASY INSTALLATION

Compact in size making it suitable for crowded, complex process environments where space is at a premium, the Midas-M Gas Detector is simple to install with its plug-and-play capability.



POE PROTOCOL

The detector includes the innovative Power over Ethernet (PoE) protocol — a single Ethernet connection for all power, control and communication requirements.



INTEGRATED SECURITY

The Midas-M Gas Detector's interface includes password-protected menus to maintain system integrity.

C4M COMÉRCIO E SERVIÇOS DE EQUIPAMENTOS

R. Conceição, 718 - Santo Antônio, São Caetano do Sul - SP | Cep: 09530-060 | Tel: (11) 3565-5579 | www.c4m.com.br



c4mequipamentos



c4msolucoesdotrabalho

Midas®-M Specifications

TABLE 1.

TRANSMITTER DIMENSION

| | |
|----------------------------|---|
| Size (unit with Cartridge) | 136 mm (H) x 83 mm (W) x 152 mm (D) (5.35 in x 3.27in x 5.98 in) |
| Weight - Transmitter | 1.3 kg (2.87 lb) |
| Weight - Cartridge | 0.17 kg ~ 0.22 kg (0.38 lb ~ 0.49 lb) dependent on sensor type |

OPTIONAL RELAY DIMENSION

| | |
|--------|---|
| Size | 137 mm (H) x 84 mm (W) x 41 mm (D) (5.39 in x 3.31 in x 1.61 in) |
| Weight | 0.31 kg (0.68 lb) |

POWER REQUIREMENTS

| | |
|--|---|
| Operating Voltage | 24 VDC Nominal, -15 to 10% (20.4 VDC to 26.4 VDC) |
| Operating Voltage with Power Over Ethernet (PoE) | 48 VDC PoE (IEEE 802.3af compliant) |

POWER CONSUMPTION

| | |
|---|-----------|
| Transmitter unit (normal condition) ¹ | Typ. 5 W |
| Transmitter unit (full load condition) ² | ≤ 11.45 W |
| Transmitter with Optional Relay | ≤ 12.9 W |

OUTPUTS

| | |
|--------------------------|---|
| Visual | Alarm, Power, Fault LEDs, and LCD with all the gas readings and events. LEDs: Power (Green), Alarm 1 (Red), Alarm 2 (Red), Fault (Yellow) |
| Relays in Transmitter | (3) Relays for Alarm 1, Alarm 2 and Fault rated 1.0 A @ 30 Vdc or 0.5 A @ 125 Vac Max 10 uA @ 10 mV minimum, configurable as normally open or closed, latched or unlatched |
| Relays in Optional Relay | 8 relays for Alarm 1 and Alarm 2 of each channel and a relay for common fault rated 1.0 A @ 30 Vdc or 0.5 A @ 125 Vac Max 10 uA @ 10 mV minimum, configurable as normally open or closed, latched or unlatched |
| Analog | 3 wire sink, 3 wire source, or 4 wire fully isolated; 0 mA to 21 mA for each channel |
| Digital Communications | Modbus/TCP Ethernet/Power over Ethernet (PoE) |

CERTIFICATIONS AND SPECIFICATION

CE marked
Meets EN 50270:2015+AC:2016 and EN 61000-6-4:2007+A1
ETL approved UL 61010-1:2012 Ed.3
IEEE 802.3af-2003

PERFORMANCE

Refer to individual sensor datasheets

TRANSPORT SYSTEM

| | |
|---------------------|--|
| Flow Rate | 600 mL/min |
| Transport Time | 2 seconds to 25 seconds maximum |
| Sample Line Tubing | 3.18 mm ID x 6.35 mm OD (0.125 in x 0.25 in) |
| Tubing Length | Up to 30 m (100 ft) with FEP tubing |
| Exhaust Line Tubing | 4.76 mm ID x 6.35 mm OD (0.188 in x 0.25 in) |
| Exhaust Length | Up to 30 m (100 ft) |
| Ambient Port | In line air filter required |

OPERATING TEMPERATURE

0°C to 40°C (32°F to 104°F)

WIRING REQUIREMENT

| | |
|---------|--|
| 4-20 mA | 2 wire, 14 AWG maximum |
| Digital | CAT5 Cable or equivalent: RJ45 connector |

C4M COMÉRCIO E SERVIÇOS DE EQUIPAMENTOS

R. Conceição, 718 - Santo Antônio, São Caetano do Sul - SP | Cep: 09530-060 | Tel: (11) 3565-5579 | www.c4m.com.br

Midas[®]-M Specifications

TABLE 1. (continued)

GAS CONCENTRATION DISPLAY AND INTERFACE

| | |
|-------------------|--|
| Instrument | 4-digit alphanumeric display with separate units, concentration bar graph for each channel and other icon driven indicators 4 button interface keypad |
| Remote | Internet browser access via Ethernet |

INSTALLATION DETAILS

| | |
|-----------------|--|
| Mounting | Wall mounted using pre-drilled holes on chassis. Options for DIN rail |
| Material | Cover: Plastic (Polycarbonate) Chassis/Mounting bracket: Zinc plated steel Red frame: Liquid coated aluminum |

WARRANTY

| | |
|-------------------------|---------|
| Transmitter Unit | 1 year |
| Sensor Cartridge | 2 years |

¹ Normal condition: (1) No gas alarm, (2) Without tube and pressure/vacuum

² Full load condition: (1) All 4 channels gas alarm are on, (2) Maximum tubing length and pressure/vacuum on the inlet/exhaust line

SMART SENSORS

| Gas Name | Chemical Formula | Range | Sensor Part Number |
|-----------------------|----------------------------------|--------------|--------------------|
| Hydrogen Chloride | HCl | 0 - 8 ppm | MMS-E2 |
| Boron Trichloride | BCl ₃ | 0 - 8 ppm | MMS-E2 |
| Dichlorosilane | SiH ₂ Cl ₂ | 0 - 8 ppm | MMS-E2 |
| Hydrogen Bromide | HBr | 0 - 8 ppm | MMS-E2 |
| Silane | SiH ₄ | 0 - 20 ppm | MMS-X2 |
| Disilane | Si ₂ H ₆ | 0 - 20 ppm | MMS-X2 |
| Hydrogen | H ₂ | 0 - 1000 ppm | MMS-G2 |
| Chlorine | Cl ₂ | 0 - 2 ppm | MMS-L2 |
| Ammonia | NH ₃ | 0 - 100 ppm | MMS-A2 |
| Carbon Monoxide | CO | 0 - 100 ppm | MMS-C2 |
| Phosphine | PH ₃ | 0 - 1200 ppb | MMS-R2 |
| Ozone | O ₃ | 0 - 0.4 ppm | MMS-U2 |
| Oxygen | O ₂ | 0 - 25% v/v | MMS-D2 |
| Sulfur Dioxide | SO ₂ | 0 - 8 ppm | MMS-S2 |
| Hydrogen Fluoride | HF | 0 - 12 ppm | MMS-Z2 |
| Boron Trifluoride | BF ₃ | 0 - 8 ppm | MMS-Z2 |
| Tungsten Hexafluoride | WF ₆ | 0 - 12 ppm | MMS-Z2 |

C4M COMÉRCIO E SERVIÇOS DE EQUIPAMENTOS

R. Conceição, 718 - Santo Antônio, São Caetano do Sul - SP | Cep: 09530-060 | Tel: (11) 3565-5579 | www.c4m.com.br



c4mequipamentos



c4msolucoesdotrabalho

HONEYWELL SAFETY PRODUCTS

Americas

Honeywell Analytics
405 Barclay Boulevard
Lincolnshire, IL 60069
Tel: +1 847 955 8200
Toll free: +1 800 538 0363
Fax: +1 847 955 8208
detectgas@honeywell.com

Europe, Middle East, and Africa

Life Safety Distribution AG (LSD)
Javastrasse 2
8604 Hegnau
Switzerland
Tel: +41 (0)44 943 4300
Fax: +41 (0)44 943 4398
gasdetection@honeywell.com

Asia Pacific, India

Honeywell Analytics Asia Pacific, Co., Ltd.
7F SangAm IT Tower
434 Worldcup Buk-ro, Mapo-gu
Seoul 03922
South Korea
Tel: +82 (0)2 6909 0300
Fax: +82 (0)2 2025 0388
India Tel: +91 124 4752700
analytics.ap@honeywell.com

Mainland China

Honeywell Industrial Safety Gas Detectors
Building#1, 555 Huanke Road Zhang Jiang
Hi-Tech Park Pudong New Area Shanghai
201203, China
Tel: 021-80386800
Fax: 021-60246070
gaschina@honeywell.com

Taiwan

Honeywell Taiwan Ltd
6F-2, No.8, ZiQiang S. Road, Jubei City,
30264 Taiwan
Tel: +886-3-5169284
Fax: +886-3-5169339
analytics.tw@honeywell.com

Manuals and other information about this product are available at:
www.honeywellanalytics.com/en/products/Midas-M



HIS_GAS_Midas-M_DTS_EN_1119
© 2019 Honeywell International Inc.

THE
FUTURE
IS
WHAT
WE
MAKE IT

Honeywell

C4M COMÉRCIO E SERVIÇOS DE EQUIPAMENTOS

R. Conceição, 718 - Santo Antônio, São Caetano do Sul - SP | Cep: 09530-060 | Tel: (11) 3565-5579 | www.c4m.com.br